

# Safety Data Sheet

**SHEB 43-0273A DV16**     **GREEN RAL 6011**

## SECTION 1: Identification

### Product identifier

Product name	SHEB 43-0273A DV16 <b><u>GREEN RAL 6011</u></b>
Product number	SHEB 43-0273A DV16
Brand	SHEB 43-0273A DV16

### Supplier's details

Name	SOUTHERN AEROSOLS
Address	PO BOX 67 CLEVELAND, NC 27013 USA

Telephone	704-278-9800
-----------	--------------

### Emergency phone number(s)

INFOTRAC Chemical Emergency Response System  
1-800-535-5053

## SECTION 2: Hazard identification

### Classification of the substance or mixture

#### GHS classification in accordance with OSHA (29 CFR 1910.1200)

- Flammable gases (chapter 2.2), Cat. 1
- Gases under pressure (chapter 2.5), compressed gas
- Aspiration hazard (chapter 3.10), Cat. 2
- Skin corrosion/irritation (chapter 3.2), Cat. 2
- Eye damage/irritation (chapter 3.3), Cat. 2B
- Sensitization, respiratory (chapter 3.4), Cat. 1
- Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3
- Germ cell mutagenicity (chapter 3.5), Cat. 2
- Carcinogenicity (chapter 3.6), Cat. 2
- Specific target organ toxicity, repeated exposure (chapter 3.9), Cat. 1
- Hazardous to the aquatic environment - acute hazard (chapter 4.1), Cat. 3

#### GHS label elements, including precautionary statements

#### Pictogram

**Safety Data Sheet**  
**SHEB 43-0273A DV16**



**Signal word**

**Danger**

**Hazard statement(s)**

H222	Extremely flammable aerosol
H280	Contains gas under pressure; may explode if heated
H305	May be harmful if swallowed and enters airways
H315	Causes skin irritation
H320	Causes eye irritation
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H341	Suspected of causing genetic defects
H351	Suspected of causing cancer
H372	Causes damage to organs through prolonged or repeated exposure
H402	Harmful to aquatic life

**Precautionary statement(s)**

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash ... thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	[In case of inadequate ventilation] wear respiratory protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/...
P302+P352	IF ON SKIN: Wash with plenty of water/...
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER/doctor/... if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P321	Specific treatment (see ... on this label).
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor/...
P362+P364	Take off contaminated clothing and wash it before reuse.
P377	Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381	Eliminate all ignition sources if safe to do so.
P403	Store in a well ventilated place.
P403+P233	Store in a well ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+P403	Protect from sunlight. Store in a well ventilated place.
P501	Dispose of contents/container to ...

**Other hazards which do not result in classification**

## SECTION 3: Composition/information on ingredients

### Mixtures

#### Hazardous components

Component	Concentration
<b>ACETONE (CAS no.: 67-64-1; EC no.: 200-662-2; Index no.: 606-001-00-8)</b>	<b>50 - &lt; 65 %</b>
CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 2; Eye damage/irritation (chapter 3.3), Cat. 2; Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3. HAZARDS: H225 - Highly flammable liquid and vapor; H319 - Causes serious eye irritation; H336 - May cause drowsiness or dizziness.	
<b>Propane, liquid (CAS no.: 74-98-6; EC no.: 200-827-9; Index no.: 601-003-00-5)</b>	<b>20 - &lt; 30 %</b>
CLASSIFICATIONS: Flammable gases (chapter 2.2), Cat. 1; Press. Gas. HAZARDS: H220 - Extremely flammable gas.	
<b>METHYL ETHYL KETONE (CAS no.: 78-93-3; EC no.: 201-159-0; Index no.: 606-002-00-3)</b>	<b>5 - &lt; 10 %</b>
CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 2; Eye damage/irritation (chapter 3.3), Cat. 2; Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3. HAZARDS: H225 - Highly flammable liquid and vapor; H319 - Causes serious eye irritation; H336 - May cause drowsiness or dizziness.	
<b>XYLENES (MIXED) (CAS no.: 1330-20-7; EC no.: 215-535-7; Index no.: 601-022-00-9)</b>	<b>25 %</b>
CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 3; Acute toxicity (chapter 3.1), Cat. 4; Skin corrosion/irritation (chapter 3.2), Cat. 2. HAZARDS: H226 - Flammable liquid and vapor; H312 - Harmful in contact with skin; H315 - Causes skin irritation; H332 - Harmful if inhaled.	
<b>ETHYLBENZENE (CAS no.: 100-41-4; EC no.: 202-849-4; Index no.: 601-023-00-4)</b>	<b>6 %</b>
CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 2; Acute toxicity (chapter 3.1), Cat. 4. HAZARDS: H225 - Highly flammable liquid and vapor; H332 - Harmful if inhaled.	
<b>TOLUENE (CAS no.: 108-88-3; EC no.: 203-625-9; Index no.: 601-021-00-3)</b>	<b>7 %</b>
CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 2; Toxic to reproduction (chapter 3.7), Cat. 2; Aspiration hazard (chapter 3.10), Cat. 1; Specific target organ toxicity, repeated exposure (chapter 3.9), Cat. 2; Skin corrosion/irritation (chapter 3.2), Cat. 2; Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3. HAZARDS: H225 - Highly flammable liquid and vapor; H304 - May be fatal if swallowed and enters airways; H315 - Causes skin irritation; H336 - May cause drowsiness or dizziness; H361d - Suspected of damaging the unborn child; H373 - May cause damage to organs through prolonged or repeated exposure.	
<b>1,2,4-Trimethylbenzene (CAS no.: 95-63-6; EC no.: 202-436-9; Index no.: 601-043-00-3)</b>	<b>2 %</b>
CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 3; Acute toxicity (chapter 3.1), Cat. 4; Eye damage/irritation (chapter 3.3), Cat. 2; Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3; Skin corrosion/irritation (chapter 3.2), Cat. 2; Hazardous to the aquatic environment - long-term hazard (chapter 4.1), Cat. 2. HAZARDS: H226 - Flammable liquid and vapor; H315 - Causes skin irritation; H319 - Causes serious eye irritation; H332 - Harmful if inhaled; H335 - May cause respiratory irritation; H411 - Toxic to aquatic life with long lasting effects.	

## SECTION 4: First-aid measures

### Description of necessary first-aid measures

General advice	Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.
If inhaled	If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.
In case of skin contact	Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.
In case of eye contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
If swallowed	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.
Personal protective equipment for first-aid responders	Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

### Most important symptoms/effects, acute and delayed

# Safety Data Sheet

## SHEB 43-0273A DV16

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

### **Indication of immediate medical attention and special treatment needed, if necessary**

Consult a physician. Show this safety data sheet to the doctor in attendance.

---

## **SECTION 5: Fire-fighting measures**

### **Suitable extinguishing media**

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

### **Specific hazards arising from the chemical**

Carbon oxides

### **Special protective actions for fire-fighters**

Wear self-contained breathing apparatus for firefighting if necessary.

### **Further information**

Use water spray to cool unopened containers.

---

## **SECTION 6: Accidental release measures**

### **Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

### **Environmental precautions**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

### **Methods and materials for containment and cleaning up**

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

### **Reference to other sections**

For disposal see section 13.

---

## **SECTION 7: Handling and storage**

### **Precautions for safe handling**

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

### **Conditions for safe storage, including any incompatibilities**

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Storage class (TRGS 510): Flammable liquids

### **Specific end use(s)**

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

---

## **SECTION 8: Exposure controls/personal protection**

### **Control parameters**

# Safety Data Sheet

## SHEB 43-0273A DV16

### CAS: 100-41-4

Ethyl benzene

Cal/OSHA: 100 ppm, (ST) 125 ppm PEL inhalation; NIOSH: 100 ppm, (ST) 125 ppm REL inhalation; OSHA: 100 ppm PEL inhalation; 435 mg/m<sup>3</sup> PEL inhalation

### CAS: 108-88-3

Toluene

Cal/OSHA: See Annotated Z-2 PEL inhalation; NIOSH: See Annotated Z-2 REL inhalation; OSHA: See Annotated Z-2 ppm PEL inhalation; See Annotated Z-2 mg/m<sup>3</sup> PEL inhalation

### CAS: 1330-20-7

Xylenes (o-, m-, p-isomers)

Cal/OSHA: 100 ppm, (ST) 150 ppm, (C) 300 ppm PEL inhalation; NIOSH: 100 ppm, (ST) 150 ppm REL inhalation; OSHA: 100 ppm PEL inhalation; 435 mg/m<sup>3</sup> PEL inhalation

### CAS: 67-64-1

Acetone

Cal/OSHA: 500 ppm, (ST) 750 ppm, (C) 3000 ppm PEL inhalation; NIOSH: 250 ppm REL inhalation; OSHA: 1000 ppm PEL inhalation; 2400 mg/m<sup>3</sup> PEL inhalation

### CAS: 74-98-6

Propane

Cal/OSHA: 1000 ppm PEL inhalation; NIOSH: 1000 ppm REL inhalation; OSHA: 1000 ppm PEL inhalation; 1800 mg/m<sup>3</sup> PEL inhalation

### CAS: 78-93-3

2-Butanone (Methyl ethyl ketone)

Cal/OSHA: 200 ppm, (ST) 300 ppm PEL inhalation; NIOSH: 200 ppm, (ST) 300 ppm REL inhalation; OSHA: 200 ppm PEL inhalation; 590 mg/m<sup>3</sup> PEL inhalation

### Appropriate engineering controls

Distribution, Workplace and Household Settings: Ensure adequate ventilation. Product Manufacturing Plant (needed at Product-Producing Plant ONLY): Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

### Individual protection measures, such as personal protective equipment (PPE)

#### Eye/face protection

Face shield and safety glasses. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

#### Body protection

Impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the

# Safety Data Sheet

## SHEB 43-0273A DV16

respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

### Thermal hazards

No data available

### Environmental exposure controls

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

---

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

Appearance/form	AEROSOL/LIQUID
Odor	TYPICAL PAINT SOLVENTS
Odor threshold	NOT AVAILABLE
pH	7
Melting point/freezing point	NOT AVAILABLE
Initial boiling point and boiling range	132-295 F
Flash point	CLOSED CUP: -20.2F
Evaporation rate	5.6 (butyl acetate = 1)
Flammability (solid, gas)	NOT AVAILABLE
Upper/lower flammability limits	12.8%/1%
Upper/lower explosive limits	13%/1%
Vapor pressure	13.5 kPa
Vapor density	1.55 (AIR = 1)
Relative density	8.0144
Solubility(ies)	SOLUBLE IN SOLVENT
Partition coefficient: n-octanol/water	NOT AVAILABLE
Auto-ignition temperature	>500 F
Decomposition temperature	NOT AVAILABLE
Viscosity	<0.07cm <sup>2</sup> /s (room temperature)
Explosive properties	
Oxidizing properties	

---

## SECTION 10: Stability and reactivity

### Reactivity

None under normal use conditions.

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

Vapours may form explosive mixture with air.

### Conditions to avoid

Heat, flames and sparks.

### Incompatible materials

Bases, Oxidizing agents, Reducing agents, Acetone reacts violently with phosphorous oxychloride.

### Hazardous decomposition products

Other decomposition products - No data available In the event of fire: see section 5

## **SECTION 11: Toxicological information**

### **Information on toxicological effects**

#### **Acute toxicity**

ACETONE

LD50 Oral - Rat - 5,800 mg/kg

Remarks: Behavioral:Altered sleep time (including change in righting reflex). Behavioral:Tremor.

Behavioral:Headache.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

ACETONE

LC50 Inhalation - Rat - 50,100 mg/m<sup>3</sup> - 8 h

Remarks: Drowsiness Dizziness Unconsciousness

ACETONE

LD50 Skin - Guinea pig - 7,429 mg/kg

XYLENES (MIXED)

LD50 Skin - Rabbit - >1.7g/kg

METHYL ETHYL KETONE

LD50 Skin - Rabbit - 6480 mg/kg

ETHYLBENZENE

LC50 Inhalation - Rat - 4000 ppg - 4 hrs

XYLENES (MIXED)

LC50 Inhalation - Rat - 6670 ppm - 4 hrs

METHYL ETHYL KETONE

LD50 Oral - Rat - 2737 mg/kg

XYLENES (MIXED)

LD50 Oral - Rat - 4.3 g/kg

ETHYLBENZENE

LD50 Skin - Rabbit - 17.8 g/kg

ETHYLBENZENE

LD50 Oral - Rat - 3.5 g/kg

TOLUENE

LC50 Inhalation - Rat - 49 g/m<sup>3</sup> - 4 hrs

TOLUENE

LC50 Inhalation - Rat - 8000 ppm - 4 hrs

TOLUENE

LD50 Skin - Rabbit - 8.39 g/kg

TOLUENE

LD50 Oral - Rat - 636 mg/kg

#### **Skin corrosion/irritation**

**Safety Data Sheet**  
**SHEB 43-0273A DV16**

ACETONE

Skin - Rabbit - 24 hr  
Result: Mild skin irritation

ACETONE

Eyes - Human - 186300 ppm  
Remarks: May cause drowsiness or dizziness.

METHYL ETHYL KETONE

Skin - Rabbit - 24 hrs 14 milligrams  
Result: Mild Irritant

**Serious eye damage/irritation**

ACETONE

- Rabbit - 24 hr  
Result: Eye irritation

**Respiratory or skin sensitization**

ACETONE

- Guinea pig  
Result: Does not cause skin sensitisation

**Germ cell mutagenicity**

ACETONE

Result: No data available

**Carcinogenicity**

ACETONE

Remarks: This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**Reproductive toxicity**

ACETONE

**Summary of evaluation of the CMR properties**

ACETONE

Remarks: This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**STOT-single exposure**

ACETONE



# Safety Data Sheet

## SHEB 43-0273A DV16

Remarks: May cause drowsiness or dizziness.

### **STOT-repeated exposure**

ACETONE

Result: No data available

### **Aspiration hazard**

No data available.

### **Additional information**

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

---

## **SECTION 12: Ecological information**

### **Toxicity**

ACETONE

LC50 - Oncorhynchus mykiss (rainbow trout) - 5,540 mg/l - 96 h

ACETONE

LC50 - Daphnia magna (Water flea) - 8,800 mg/l - 48 hr

### **Persistence and degradability**

ACETONE

OECD Test Guideline 301B

Result: 91% -Readily biodegradable.

### **Bioaccumulative potential**

Does not bioaccumulate.

### **Mobility in soil**

No data available.

### **Results of PBT and vPvB assessment**

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

### **Other adverse effects**

No data available

---

## **SECTION 13: Disposal considerations**

### **Disposal of the product**

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

### **Disposal of contaminated packaging**

Dispose of as unused product.

### **Waste treatment**

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

# Safety Data Sheet

## SHEB 43-0273A DV16

### Sewage disposal

Dispose of contents/ container in accordance with the local/regional/national/international regulations. Non Household Setting: Products covered by this SDS, in their original form, when disposed as waste, are considered non hazardous waste according to Federal RCRA regulations (40 CFR 261). Disposal should be in accordance with local, state and federal regulations. Solutions of diluted detergent in the course of use, may be allowed to be flushed down sewer. First check with your local water treatment plant. Recycling is undiluted scrap product. Do not landfill. Household Use: Household product is safe for disposal down the drain during detergent use or in the trash. Dispose of empty bottle in the trash or recycle where facilities exist.

### Other disposal recommendations

Check with all related government agencies.

---

## SECTION 14: Transport information

### DOT (US)

UN Number: 1950

Class: 2.1

Packing Group:

Proper Shipping Name: AEROSOLS

Reportable quantity (RQ): Special Provisions: LIMITED QUANTITY

Marine pollutant: NO

Poison inhalation hazard:

### IMDG

UN Number: 1950

Class: 2.1

Packing Group:

EMS Number:

Proper Shipping Name: AEROSOLS

### IATA

UN Number: 1950

Class: 2.1

Packing Group:

Proper Shipping Name: AEROSOLS, FLAMMABLE

---

## SECTION 15: Regulatory information

### Safety, health and environmental regulations specific for the product in question

#### California Prop. 65 components

#### Massachusetts Right To Know Components

Chemical name: Acetone

CAS number: 67-64-1. Chemical name: Methyl ethyl ketone

CAS number: 78-93-3. Chemical name: Xylene (mixed isomers)

CAS number: 1330-20-7. Chemical name: Ethylbenzene

CAS number: 100-41-4. Chemical name: Toluene

CAS number: 108-88-3. Chemical name: 1,2,4-Trimethylbenzene

CAS number: 95-63-6

#### New Jersey Right To Know Components

Common name: ACETONE

CAS number: 67-64-1. Common name: PROPANE

CAS number: 74-98-6. Common name: METHYL ETHYL KETONE

# Safety Data Sheet

## SHEB 43-0273A DV16

CAS number: 78-93-3. Common name: XYLENES  
CAS number: 1330-20-7. Common name: ETHYL BENZENE  
CAS number: 100-41-4. Common name: TOLUENE  
CAS number: 108-88-3. Common name: PSEUDOCUMENE  
CAS number: 95-63-6

### Pennsylvania Right To Know Components

Chemical name: 2-Propanone  
CAS number: 67-64-1. Chemical name: Propane  
CAS number: 74-98-6. Chemical name: 2-Butanone  
CAS number: 78-93-3. Chemical name: Benzene, dimethyl-  
CAS number: 1330-20-7. Chemical name: Benzene, ethyl-  
CAS number: 100-41-4. Chemical name: Benzene, methyl-  
CAS number: 108-88-3. Chemical name: Pseudocumene  
CAS number: 95-63-6

### Stockholm Convention

#### HMIS Rating

Health	2
Flammability	4
Physical hazard	0
Personal protection	X

#### NFPA Rating

Health hazard	2
Fire hazard	3
Reactivity hazard	
Special hazard	

---

## SECTION 16: Other information

DISCLAIMER: The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of information for their particular purposes. In no event shall Southern Aerosols/Custom Aero Coatings be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, whatsoever arising, even if [COMPANY NAME] has been advised of the possibility of such damages.

#### Further information/disclaimer

No data available.

#### Preparation information

No data available.